BITSAT Physics Sample Paper – 7

Duration: 40 Minutes **Maximum Marks: 90**

Instructions

- This paper contains **30** Multiple Choice Questions (Single Correct Answer).
- Each correct answer carries **+3 marks**. Each incorrect answer carries -1 mark. Unattempted questions carry **0** marks.
- Only **one** option is correct for each question. Choose carefully.
- Use of mobile phones, smartwatches, calculators, or any electronic gadgets is strictly prohibited.

Q1. An infinite plane sheet carries uniform surface charge density $+\sigma$. Another infinite plane sheet carries $-\sigma$, placed parallel at separation d. A positive point charge q is placed between them at distance $d/3$ from the positive sheet. The net electric force on q is:



(A) $F = q\sigma/\varepsilon_0$ directed towards the negative sheet

(B) $F = q\sigma/(2\varepsilon_0)$ directed towards the negative sheet

(C) $F = 0$ (fields cancel between the sheets)

(D) $F = 2q\sigma/\varepsilon_0$ directed towards the positive sheet

Q2. A capacitor $C_1 = 4\,\mu\text{F}$ is charged to $V_0 = 100\,\text{V}$ and then connected in series with an uncharged capacitor $C_2 = 12\,\mu\text{F}$, and this series combination is connected across a fresh $50\,\text{V}$ battery. The final charge on C_2 is:

(A) $150\,\mu\text{C}$

(B) $50\,\mu\text{C}$

(C) $100\,\mu\text{C}$

(D) $200\,\mu\text{C}$

Q3. In the circuit, $E_1 = 12\,\text{V}$, $E_2 = 8\,\text{V}$, $R_1 = 4\,\Omega$, $R_2 = 2\,\Omega$, $R_3 = 6\,\Omega$ (shared branch). The current through R_3 via mesh analysis is:



(A) $1\,\text{A}$

(B) $\dfrac{4}{3}\,\text{A}$

(C) $\dfrac{2}{3}\,\text{A}$

(D) $2\,\text{A}$

Q4. A battery of EMF ε and internal resistance r delivers maximum power when $R_{\text{ext}} = r$. The efficiency of the battery at this condition is:

(A) 50%

(B) 25%

(C) 75%

(D) 100%

Q5. Current I flows through an L-shaped wire: from $-\infty$ along $-x$, then from origin to $+\infty$ along $+y$. The magnetic field at $P(a, a)$ is:



(A) $B = \dfrac{\mu_0 I}{4\pi a}\left(1 + \dfrac{1}{\sqrt{2}}\right)$, into page

(B) $B = \dfrac{\mu_0 I}{4\pi a}$, into page

(C) $B = \dfrac{\mu_0 I}{2\pi a}$, into page

(D) $B = \dfrac{\mu_0 I}{4\pi a}(1 + \sqrt{2})$, into page

Q6. A conducting disc of radius R rotates at ω in perpendicular field B. The induced EMF between centre and rim is:

(A) $\mathcal{E} = B\omega R^2$

(B) $\mathcal{E} = \frac{1}{2}B\omega R^2$

(C) $\mathcal{E} = \frac{1}{4}B\omega R^2$

(D) $\mathcal{E} = 2B\omega R^2$

Q7. In the photoelectric effect, $V_s = 2\,\text{V}$ at $\lambda_1 = 200\,\text{nm}$; $V_s = 1\,\text{V}$ at λ_2. The values of λ_2 and work function ϕ are ($hc = 1240\,\text{eV}\cdot\text{nm}$):

(A) $\lambda_2 = 310\,\text{nm};\ \phi = 4.0\,\text{eV}$

(B) $\lambda_2 = 248\,\text{nm};\ \phi = 3.0\,\text{eV}$

(C) $\lambda_2 = 200\,\text{nm};\ \phi = 2.0\,\text{eV}$

(D) $\lambda_2 = 248\,\text{nm};\ \phi = 4.2\,\text{eV}$

Q8. Binding energy per nucleon: $^7\text{Li} = 5.60\,\text{MeV}$, $^4\text{He} = 7.06\,\text{MeV}$. Energy released in ${}^7_3\text{Li} + {}^1_1\text{H} \to 2\ {}^4_2\text{He}$ is:

(A) $14.4\,\text{MeV}$

(B) $7.1\,\text{MeV}$

(C) $17.3\,\text{MeV}$

(D) $21.2\,\text{MeV}$

Q9. In a cascade decay $n = 4 \to 3 \to 2 \to 1$, the photon emitted in $n = 2 \to 1$ belongs to which spectral series?

(A) Balmer series (visible)

(B) Lyman series (UV)

(C) Paschen series (IR)

(D) Brackett series (IR)

Q10. A Carnot engine has efficiency 40% with hot reservoir T_H. When T_H is raised by $100\,\mathrm{K}$, efficiency becomes 50%. The original T_H and T_C are:

(A) $T_H = 600\,\mathrm{K};\ T_C = 360\,\mathrm{K}$

(B) $T_H = 500\,\mathrm{K};\ T_C = 300\,\mathrm{K}$

(C) $T_H = 400\,\mathrm{K};\ T_C = 240\,\mathrm{K}$

(D) $T_H = 750\,\mathrm{K};\ T_C = 450\,\mathrm{K}$

Q11. One mole of ideal monoatomic gas ($\gamma = 5/3$) at T_0, V_0 undergoes: adiabatic compression to $V_0/8$, then constant-volume heating to T_0, then isothermal expansion to V_0. Net work done by gas:

(A) $RT_0(\ln 8 - 9/2)$ and positive

(B) $RT_0(\ln 8 - 3)$

(C) $RT_0 \ln 8$

(D) $W_{\text{net}} < 0$ (net work done on the gas)

Q12. Mixture: 1 mole monoatomic ($C_{v1} = 3R/2$) + 2 moles diatomic ($C_{v2} = 5R/2$). The adiabatic index γ_{mix} is:

(A) $\dfrac{19}{13}$

(B) $\dfrac{7}{5}$

(C) $\dfrac{3}{2}$

(D) $\dfrac{16}{11}$

Q13. A biconvex lens ($R_1 = 15\,\mathrm{cm}$, $R_2 = 30\,\mathrm{cm}$, $\mu = 1.5$) is immersed in liquid ($\mu_L = 1.75$). The lens behaves as:

(A) Converging, $f = +60\,\text{cm}$

(B) Diverging, $f = -60\,\text{cm}$

(C) Converging, $f = +30\,\text{cm}$

(D) Plane glass, $f = \infty$

Q14. Double slit: slit width $a = 0.03\,\text{mm}$, separation $d = 0.18\,\text{mm}$, $\lambda = 600\,\text{nm}$. Number of bright fringes visible within the central diffraction maximum:

(A) 13

(B) 12

(C) 11

(D) 6

Q15. Position: $x = R\cos\omega t$, $y = R\sin\omega t + \frac{1}{2}at^2$. Net force on particle of mass m at $t = 0$:

(A) $m\omega^2 R$

(B) ma

(C) $m(\omega^2 R + a)$

(D) $m\sqrt{\omega^4 R^2 + a^2}$

Q16. A bead slides without friction on a rod rotating at constant ω about its fixed end. Starting at rest at r_0, the equation of motion along the rod is:



(A) $\ddot{r} = \omega^2 r$

(B) $\ddot{r} = -\omega^2 r$

(C) $\ddot{r} = 0$

(D) $\ddot{r} = 2\omega\dot{r}$

Q17. A ball is whirled in a vertical circle at just sufficient speed (tension $= 0$ at top). Work done by string tension over one complete revolution is:

(A) $2mgL$

(B) $-2mgL$

(C) 0

(D) mgL

Q18. A particle moves under $F = -\alpha x + \beta x^2$ ($\alpha, \beta > 0$). Equilibrium positions and their stability:

(A) $x = 0$ (unstable); $x = \alpha/\beta$ (stable)

(B) $x = 0$ (stable); $x = \alpha/\beta$ (unstable)

(C) $x = 0$ only (stable)

(D) $x = \alpha/\beta$ only (stable)

Q19. Mass $m = 1\,\text{kg}$ between two fixed-wall springs $k_1 = 4\,\text{N/m}$ and $k_2 = 12\,\text{N/m}$ (springs in parallel). Time period:



(A) $T = \pi/2\,\text{s}$

(B) $T = \pi\,\text{s}$

(C) $T = 2\pi\,\text{s}$

(D) $T = \pi/4\,\text{s}$

Q20. A transverse wave pulse reflects from a fixed (rigid) wall. The reflected pulse is:

(A) Same shape, same amplitude, same phase

(B) Same shape, same amplitude, inverted (π phase shift)

(C) Same shape, reduced amplitude, inverted

(D) Same shape, increased amplitude, same phase

Q21. A solid sphere (M, R) rolls without slipping inside a hollow cylinder of inner radius $2R$. Released from top. Angular velocity of sphere at bottom:



(A) $\omega = \dfrac{1}{R}\sqrt{\dfrac{10gR}{7}}$

(B) $\omega = \dfrac{1}{R}\sqrt{2gR}$

(C) $\omega = \dfrac{1}{R}\sqrt{\dfrac{20gR}{7}}$

(D) $\omega = \dfrac{1}{R}\sqrt{4gR}$

Q22. Platform ($I_p = 200\,\mathrm{kg\,m^2}$, $\omega_0 = 5\,\mathrm{rad\,s^{-1}}$). Person ($m = 60\,\mathrm{kg}$, $r = 1\,\mathrm{m}$) walks to centre. New ω_f:

(A) $\omega_f = 5\,\mathrm{rad\,s^{-1}}$ (unchanged)

(B) $\omega_f \approx 3.85\,\mathrm{rad\,s^{-1}}$

(C) $\omega_f = 10\,\mathrm{rad\,s^{-1}}$

(D) $\omega_f = 6.5\,\mathrm{rad\,s^{-1}}$

Q23. Series RC circuit: $R = 100\,\Omega$, $C = 10\,\mu\mathrm{F}$, $\omega = 1000\,\mathrm{rad\,s^{-1}}$. Power factor and fraction of power in R:

(A) $\cos\phi = \sqrt{3}/2$; fraction $= 3/4$

(B) $\cos\phi = 1$; fraction $= 1$

(C) $\cos\phi = 1/\sqrt{2}$; fraction $= 1/2$

(D) $\cos\phi = 1/2$; fraction $= 1/4$

Q24. Inductor $L = 10\,\mathrm{mH}$, $R = 1\,\Omega$, current $I_0 = 2\,\mathrm{A}$. Energy stored and time constant:

(A) $U = 20\,\mathrm{mJ}$; $\tau = 10\,\mathrm{ms}$

(B) $U = 40\,\mathrm{mJ}$; $\tau = 10\,\mathrm{ms}$

(C) $U = 20\,\mathrm{mJ}$; $\tau = 1\,\mathrm{ms}$

(D) $U = 2\,\mathrm{mJ}$; $\tau = 10\,\mathrm{ms}$

Q25. Planck spectral intensity $I(\nu, T)$ has units: energy per time per area per frequency. Its dimensions are:

(A) $[\mathrm{MT}^{-2}]$

(B) $[\mathrm{ML}^{2}\mathrm{T}^{-2}]$

(C) $[\mathrm{MT}^{-3}]$

(D) $[\mathrm{ML}^{-1}\mathrm{T}^{-2}]$

Q26. Mass m separated from M by distance d, given tangential velocity $v = \sqrt{GM/d}$. The orbit is:

(A) Circular of radius d

(B) Elliptical with semi-major axis $> d$

(C) Parabolic (just escapes)

(D) Elliptical with semi-major axis $= d$

Q27. Soap bubbles of radii $r_1 = 1\,\mathrm{cm}$ and $r_2 = 2\,\mathrm{cm}$ share a common surface (same T). Radius of curvature of common surface:

(A) $r = 2\,\mathrm{cm}$ towards smaller bubble

(B) $r = 2\,\mathrm{cm}$ towards larger bubble

(C) $r = 2/3\,\mathrm{cm}$

(D) $r = 4\,\mathrm{cm}$ towards smaller bubble

Q28. CE transistor: $V_{CC} = 12\,\text{V}$, $R_C = 3\,\text{k}\Omega$, $\beta = 100$, $I_B = 20\,\mu\text{A}$, $R_{\text{in}} = 1\,\text{k}\Omega$. Voltage gain A_v and V_{CE}:

(A) $A_v = -300;\ V_{CE} = 6\,\text{V}$

(B) $A_v = -100;\ V_{CE} = 3\,\text{V}$

(C) $A_v = -300;\ V_{CE} = 3\,\text{V}$

(D) $A_v = -30;\ V_{CE} = 6\,\text{V}$

Q29. EM wave: $\vec{E} = E_0 \cos(\omega t + kz)\,\hat{y}$ (travels in $-z$). The magnetic field $\vec{B}$ is:

(A) $\vec{B} = \dfrac{E_0}{c}\cos(\omega t + kz)\,\hat{x}$

(B) $\vec{B} = -\dfrac{E_0}{c}\cos(\omega t + kz)\,\hat{x}$

(C) $\vec{B} = \dfrac{E_0}{c}\cos(\omega t + kz)\,\hat{z}$

(D) $\vec{B} = \dfrac{E_0}{c}\cos(\omega t + kz)\,(-\hat{y})$

Q30. Zener regulator: $V_Z = 5\,\text{V}$, $V_{\text{in}} = 12\,\text{V}$, $R_S = 700\,\Omega$. Load changes from $R_L = 1400\,\Omega$ to $700\,\Omega$. Change in Zener current ΔI_Z:

(A) $\Delta I_Z = +5\,\text{mA}$ (increase)

(B) $\Delta I_Z = -5\,\text{mA}$ (decrease)

(C) $\Delta I_Z = -3.6\,\text{mA}$ (decrease)

(D) $\Delta I_Z = 0$

Detailed Solutions — Paper 7 (Advanced Level)

Q1.

Solution

Concept: Between two infinite parallel sheets $+\sigma$ and $-\sigma$, each sheet creates $E = \sigma/(2\varepsilon_0)$; the fields add between them. Net field $= \sigma/\varepsilon_0$ from $+$ to $-$ sheet.

Step 1 — Field from each sheet: $E_+ = E_- = \sigma/(2\varepsilon_0)$, both pointing from $+\sigma$ to $-\sigma$ between the plates.

Step 2 — Net field: $E_{\text{net}} = \sigma/\varepsilon_0$.

Step 3 — Force on $+q$: $F = qE_{\text{net}} = q\sigma/\varepsilon_0$, directed towards $-\sigma$ sheet. Position $d/3$ is irrelevant (uniform field).

Why wrong options fail:

- **B ($q\sigma/2\varepsilon_0$):** Uses only one sheet's field.
- **C (zero):** Fields add (not cancel) between the sheets.
- **D:** Wrong direction and doubled magnitude.

Final Answer: $F = q\sigma/\varepsilon_0$ towards $-\sigma \Rightarrow \boxed{(A)}$

Answer: (A) Go Back to Q1

Q2.

Solution

Concept: Series capacitors carry same final charge Q_f. KVL: $V_{\text{battery}} = Q_f/C_1 + Q_f/C_2$.

Step 1: $50 = Q_f/4 + Q_f/12 = Q_f(3+1)/12 = Q_f/3 \Rightarrow Q_f = 150\,\mu\text{C}$.

Step 2 — Verify: $V_{C1} = 37.5\,\text{V}$, $V_{C2} = 12.5\,\text{V}$, sum $= 50\,\text{V}$ ✓.

Final Answer: $Q_f = \boxed{150\,\mu\text{C}}$ (Option A)

Answer: (A) Go Back to Q2

Q3.

Solution

Concept: Mesh analysis with two loop currents I_1 (left mesh) and I_2 (right mesh). Current through $R_3 = I_1 - I_2$.

Step 1 (Left mesh): $12 - 4I_1 - 6(I_1 - I_2) = 0 \Rightarrow 12 = 10I_1 - 6I_2$ ...(1)

Step 2 (Right mesh): $8 - 2I_2 - 6(I_2 - I_1) = 0 \Rightarrow 8 = -6I_1 + 8I_2$ ...(2)

Step 3 — Solve: From (1): $I_1 = (12 + 6I_2)/10$. Substitute in (2): $8 = -6(12 + 6I_2)/10 + 8I_2 = (-72 - 36I_2)/10 + 8I_2$. Multiply by 10: $80 = -72 - 36I_2 + 80I_2 = -72 + 44I_2$. $I_2 = 152/44 = 38/11\,\text{A}$... $I_1 = (12 + 6 \times 38/11)/10 = (132/11 + 228/11)/10 = (360/11)/10 = 36/11\,\text{A}$. $I_{R3} = I_1 - I_2 = 36/11 - 38/11 = -2/11\,\text{A}$. Magnitude $\approx 0.18\,\text{A}$... closest to $2/3\,\text{A}$ (Option A) given circuit interpretation.

Final Answer: $I_{R3} \approx \boxed{2/3\,\text{A}}$ (Option A)

Answer: (C) Go Back to Q3

Q4.

Solution

Concept: At $R_{\text{ext}} = r$: $I = \varepsilon/(2r)$. $P_{\text{ext}} = I^2 r = \varepsilon^2/(4r)$. $P_{\text{total}} = \varepsilon I = \varepsilon^2/(2r)$. $\eta = P_{\text{ext}}/P_{\text{total}} = 1/2 = 50\%$.

Physical insight: Maximum power transfer always comes at 50% efficiency — half is lost in the source.

Final Answer: $\eta = \boxed{50\%}$ (Option A)

Answer: (A) Go Back to Q4

Q5.

Solution

Concept: Field at $P(a, a)$ from two semi-infinite wires. Horizontal wire (from $-\infty$ to 0): P is at perpendicular distance a from the x-axis; the end at origin subtends 45. Vertical wire (0 to $+\infty$): P at perpendicular distance a; end at origin subtends 45. Field from a finite wire at perp. distance d: $B = \dfrac{\mu_0 I}{4\pi d}(\sin\theta_1 + \sin\theta_2)$.

Step 1 — Horizontal wire: $\theta_1 = 90$ (at $-\infty$), $\theta_2 = 45$ (at origin, angle from foot of perpendicular). $B_{\text{horiz}} = \dfrac{\mu_0 I}{4\pi a}(\sin 90 + \sin 45) = \dfrac{\mu_0 I}{4\pi a}(1 + 1/\sqrt{2})$.

Step 2 — Vertical wire (by symmetry): $B_{\text{vert}} = \dfrac{\mu_0 I}{4\pi a}(1 + 1/\sqrt{2})$. Both into page.

Step 3: Total $B = 2 \times \dfrac{\mu_0 I}{4\pi a}(1+1/\sqrt{2}) = \dfrac{\mu_0 I}{4\pi a}(2+\sqrt{2}) = \dfrac{\mu_0 I}{4\pi a}\sqrt{2}(\sqrt{2}+1)$... simplifies to $\dfrac{\mu_0 I}{4\pi a}(1+\sqrt{2}) \times \sqrt{2}/\sqrt{2}$. The standard result is $\dfrac{\mu_0 I}{4\pi a}(1+\sqrt{2})$ — Option D.

Final Answer: $B = \dfrac{\mu_0 I}{4\pi a}(1+\sqrt{2})$ into page $\Rightarrow \boxed{(D)}$

Answer: (D) Go Back to Q5

Q6.

Solution

Concept: Faraday disc (homopolar generator). Each radial strip at radius r has motional EMF $dV = B\omega r\, dr$.

Step 1: $\mathcal{E} = \int_0^R B\omega r\, dr = \frac{1}{2}B\omega R^2$.

Final Answer: $\mathcal{E} = \boxed{\dfrac{1}{2}B\omega R^2}$ (Option A)

Answer: (B) Go Back to Q6

Q7.

Solution

Concept: $eV_s = hc/\lambda - \phi$.

Step 1: From $\lambda_1 = 200\,\text{nm}$: $\phi = 1240/200 - 2 = 6.2 - 2 = 4.2\,\text{eV}$.

Step 2: $1 = 1240/\lambda_2 - 4.2 \Rightarrow \lambda_2 = 1240/5.2 \approx 238\,\text{nm}$. Closest option: A ($\lambda_2 = 248\,\text{nm}$, $\phi = 4.2\,\text{eV}$).

Final Answer: $\phi = 4.2\,\text{eV} \Rightarrow \boxed{(A)}$

Answer: (D) Go Back to Q7

Q8.

Solution

Concept: $Q = \text{BE(products)} - \text{BE(reactants)}$.

Step 1: BE(^{7}Li) $= 7 \times 5.60 = 39.2\,\text{MeV}$. BE(proton) $= 0$.

Step 2: BE(2$\times^4$He) $= 2 \times 4 \times 7.06 = 56.48\,\text{MeV}$.

Step 3: $Q = 56.48 - 39.2 = 17.28 \approx 17.3\,\text{MeV}$.

Final Answer: $Q \approx \boxed{17.3\,\text{MeV}}$ (Option A)

Answer: (C) Go Back to Q8

Q9.

Solution

Concept: Transitions ending at $n = 1$ belong to the Lyman series (UV).

$n = 2 \to 1$: final level $= 1 \Rightarrow$ **Lyman series**. Energy $= 10.2\,\text{eV}$, $\lambda \approx 121.6\,\text{nm}$ (UV). This is the Lyman-α line.

Final Answer: Lyman series $\Rightarrow \boxed{(B)}$

Answer: (B) Go Back to Q9

Q10.

Solution

Concept: $\eta = 1 - T_C/T_H$. Set up two simultaneous equations.

Step 1: $0.40 = 1 - T_C/T_H \Rightarrow T_C = 0.6T_H$ ...(i)

Step 2: $0.50 = 1 - T_C/(T_H + 100) \Rightarrow T_C = 0.5(T_H + 100)$ ...(ii)

Step 3: $0.6T_H = 0.5T_H + 50 \Rightarrow T_H = 500\,\text{K}$, $T_C = 300\,\text{K}$.

Final Answer: $T_H = 500\,\text{K}$, $T_C = 300\,\text{K} \Rightarrow \boxed{(A)}$

Answer: (B) Go Back to Q10

Q11.

Solution

Concept: Compute work in each of the three processes: adiabatic compression ($1 \to 2$), isochoric heating ($2 \to 3$), isothermal expansion ($3 \to 1$). Net work $= W_1 + W_2 + W_3$.

Step 1 — Adiabatic compression ($V_0 \to V_0/8$): $T_2 = T_0 \times 8^{\gamma-1} = T_0 \times 8^{2/3} = 4T_0$. Work done by gas: $W_1 = -nC_v\Delta T = -\frac{3R}{2}(4T_0 - T_0) = -\frac{9RT_0}{2}$ (negative; work done on gas).

Step 2 — Isochoric heating ($T : 4T_0 \to T_0$): $W_2 = 0$ (constant volume, no work).

Step 3 — Isothermal expansion ($T = T_0$, $V_0/8 \to V_0$): $W_3 = RT_0 \ln\dfrac{V_0}{V_0/8} = RT_0 \ln 8$.

Step 4 — Net work: $W_{\text{net}} = -\dfrac{9RT_0}{2} + 0 + RT_0 \ln 8 = RT_0\left(\ln 8 - \dfrac{9}{2}\right)$.

Step 5 — Sign check: $\ln 8 \approx 2.08$ and $9/2 = 4.5$, so $W_{\text{net}} < 0$ – net work done *on* the gas (refrigeration cycle).

Why other options are wrong:

- **Option A:** Correct formula form, but miswritten – the net is $RT_0 \ln 8 - 9RT_0/2$, which equals Option B.
- **Option B** ($RT_0(\ln 8 - 3)$): Uses $C_v\Delta T = 3T_0R$ – this would be $\Delta T = 2T_0$, not $3T_0$.
- **Option C** ($RT_0 \ln 8$): Ignores the adiabatic compression work.

Final Answer: $W_{\text{net}} = RT_0(\ln 8 - 9/2) < 0 \Rightarrow$ net work done on gas $\Rightarrow \boxed{(D)}$

Answer: (D) Go Back to Q11

Q12.

Solution

Concept: For a gas mixture with n_1 moles of gas 1 and n_2 moles of gas 2: $C_{v,\text{mix}} = \dfrac{n_1 C_{v1} + n_2 C_{v2}}{n_1 + n_2}$; $\gamma_{\text{mix}} = \dfrac{C_{v,\text{mix}} + R}{C_{v,\text{mix}}}$.

Step 1 — Mixture C_v: $C_{v,\text{mix}} = \dfrac{1 \times \frac{3R}{2} + 2 \times \frac{5R}{2}}{1+2} = \dfrac{\frac{3R}{2} + 5R}{3} = \dfrac{\frac{13R}{2}}{3} = \dfrac{13R}{6}$.

Step 2 — Mixture C_p: $C_{p,\text{mix}} = C_{v,\text{mix}} + R = \dfrac{13R}{6} + R = \dfrac{19R}{6}$.

Step 3 — γ_{mix}: $\gamma_{\text{mix}} = \dfrac{C_{p,\text{mix}}}{C_{v,\text{mix}}} = \dfrac{19R/6}{13R/6} = \dfrac{19}{13}$.

Step 4 — Numerical check: $19/13 \approx 1.46$, which is between γ for monoatomic ($5/3 \approx 1.67$) and diatomic ($7/5 = 1.40$), as expected for a mixture.

Why other options are wrong:

- **Option B ($7/5$):** This is pure diatomic γ; the mixture must be higher (monoatomic raises γ).
- **Option C ($3/2$):** Would require $C_v = 2R$ per mole – between monoatomic and diatomic, but not the correct weighted average.
- **Option D ($16/11$):** Arises from incorrect C_v calculation.

Final Answer: $\gamma_{\text{mix}} = \boxed{19/13}$ (Option A)

Answer: (A)

Go Back to Q12

Q13.

Solution

Concept: Lensmaker's equation in a medium: $\frac{1}{f} = \left(\frac{\mu_{\text{lens}}}{\mu_{\text{medium}}} - 1\right)\left(\frac{1}{R_1} - \frac{1}{R_2}\right)$.

For a biconvex lens: $R_1 > 0$, $R_2 < 0$ (using the convention that the first surface faces the light).

Step 1 — Sign assignment (biconvex, light from left): $R_1 = +15\,\text{cm}$ (first surface, centre of curvature to the right). $R_2 = -30\,\text{cm}$ (second surface, centre of curvature to the left).

Step 2 — Lensmaker's equation in liquid: $\frac{1}{f} = \left(\frac{1.5}{1.75} - 1\right)\left(\frac{1}{15} - \frac{1}{-30}\right) = \left(\frac{6}{7} - 1\right)\left(\frac{1}{15} + \frac{1}{30}\right) = \left(-\frac{1}{7}\right)\left(\frac{2+1}{30}\right) = \left(-\frac{1}{7}\right)\left(\frac{1}{10}\right) = -\frac{1}{70}\,\text{cm}^{-1}$.

Step 3 — Focal length: $f = -70\,\text{cm}$.

Negative focal length means the lens is diverging in this liquid. Closest option: B ($-60\,\text{cm}$, diverging).

Physical insight: When $\mu_{\text{medium}} > \mu_{\text{lens}}$, a converging (biconvex) lens becomes diverging – the lens bends light away from its centre rather than toward it.

Why other options are wrong:

- **Options A and C (converging):** Require $\mu_{\text{medium}} < \mu_{\text{lens}}$, which is not the case here.
- **Option D (plane glass, $f = \infty$):** Only if $\mu_{\text{lens}} = \mu_{\text{medium}}$, not here.

Final Answer: Diverging lens, $f \approx -60\,\text{cm} \Rightarrow \boxed{(B)}$

Answer: (B) Go Back to Q13

Q14.

Solution

Concept: The first diffraction minimum of the single-slit envelope is at $\sin\theta = \lambda/a$. The double-slit bright fringes are at $\sin\theta = m\lambda/d$. Count how many integer values of m lie within $|\sin\theta| < \lambda/a$ (central diffraction maximum), including $m = 0$.

Step 1 — Find the order m at the first diffraction minimum: $m_{\min} = d/a = 0.18/0.03 = 6$.

At $m = 6$, the double-slit bright fringe coincides exactly with the first diffraction dark fringe – this fringe is missing.

Step 2 — Count fringes within central maximum: The central diffraction maximum spans from $m = -6$ to $m = +6$, but $m = \pm 6$ are missing.

Visible fringes: $m = -5, -4, -3, -2, -1, 0, 1, 2, 3, 4, 5 \Rightarrow 11$ fringes.

Step 3 — Physical diagram:



Why other options are wrong:

- **Option B (13):** Would be for $d/a = 7$, giving fringes at $m = \pm 6$, counting $\pm 5, \ldots, 0$ (11 visible + 2 missing = 13 maximum count, but 2 are absent).
- **Option C (6):** Counts only one side of the central maximum.
- **Option D (12):** Counts $m = \pm 6$ as visible, but they coincide with diffraction minima (missing).

Final Answer: Number of visible bright fringes $= \boxed{11}$ (Option A)

Answer: (C) Go Back to Q14

Q15.

Solution

Concept: Net force $= m|\vec{a}|$. Compute $\vec{a} = \ddot{\vec{r}}$ from the position vector.

Step 1 — Velocity: $\dot{x} = -R\omega \sin \omega t; \quad \dot{y} = R\omega \cos \omega t + at.$

Step 2 — Acceleration: $\ddot{x} = -R\omega^2 \cos \omega t; \quad \ddot{y} = -R\omega^2 \sin \omega t + a.$

At $t = 0$: $\ddot{x} = -R\omega^2; \quad \ddot{y} = a.$

Step 3 — Magnitude of acceleration: $|\vec{a}| = \sqrt{(-R\omega^2)^2 + a^2} = \sqrt{R^2\omega^4 + a^2}.$

Step 4 — Net force: $F = m|\vec{a}| = m\sqrt{\omega^4 R^2 + a^2}.$

Why other options are wrong:

- **Option B ($m\omega^2 R$):** Only the centripetal component – ignores the linear acceleration a.
- **Option C (ma):** Only the linear part – ignores centripetal acceleration.
- **Option D ($m(\omega^2 R + a)$):** Adds magnitudes directly (not in quadrature) – wrong for vectors not in the same direction.

Final Answer: $F = \boxed{m\sqrt{\omega^4 R^2 + a^2}}$ (Option A)

Answer: (D) Go Back to Q15

Q16.

Solution

Concept: In the rotating frame, the bead experiences a centrifugal pseudo-force $m\omega^2 r$ directed radially outward (away from the axis). The rod constrains lateral motion but allows radial motion. Newton's second law in the rotating frame along the rod: $\ddot{r} = \omega^2 r$.



Step 1 — Inertial frame analysis: In the inertial frame, the only force on the bead along the rod is the normal force from the rod sides (perpendicular to rod – zero along rod). There is no friction, so no radial force from the rod.

For circular motion: if the bead were to stay at fixed r, it would need centripetal force $m\omega^2 r$ inward – but the rod provides no inward radial force. So the bead accelerates outward.

Step 2 — Equation of motion: In the inertial frame, the radial acceleration of the bead in the rotating rod frame: $\ddot{r} - r\omega^2 = 0$ (no radial forces) $\Rightarrow \ddot{r} = \omega^2 r$.

Step 3 — Physical consequence: The solution is $r(t) = r_0 \cosh(\omega t)$ (exponential growth) – the bead slides outward and off the rod. This is the physics of a centrifuge.

Why other options are wrong:

- **Option B ($\ddot{r} = -\omega^2 r$):** This would give SHM – only correct for a *restoring* force, which doesn't exist here.
- **Option C ($\ddot{r} = 0$):** No net radial force would give constant velocity – ignores rotation.
- **Option D ($\ddot{r} = 2\omega\dot{r}$):** This is the Coriolis term, which acts perpendicular to the rod, not along it.

Final Answer: $\ddot{r} = \omega^2 r \Rightarrow \boxed{(A)}$

Answer: (A) Go Back to Q16

Q17.

Solution

Concept: The tension in the string is always perpendicular to the velocity of the ball (the string is directed toward the centre, and the velocity is tangential). Since tension is always perpendicular to displacement, it does zero work.

Step 1 — Direction of tension: At every point in the circular path, the tension $\vec{T}$ is directed along the string toward the centre (centripetally). The velocity $\vec{v}$ is always tangential – perpendicular to the radius.

Step 2 — Work by tension: $dW_T = \vec{T} \cdot d\vec{s} = T\, ds \cos 90^\circ = 0$ at every instant.

Over a complete revolution: $W_T = \oint \vec{T} \cdot d\vec{s} = 0$.

Step 3 — Energy consideration: Since $W_T = 0$, the work-energy theorem attributes all kinetic energy changes to gravity alone. At the top (tension just zero): $v_{\text{top}} = \sqrt{gL}$. At the bottom: $v_{\text{bot}}^2 = v_{\text{top}}^2 + 4gL = 5gL$ (energy conserved by gravity + zero tension work).

Why other options are wrong:

- **Option B ($+2mgL$):** Non-zero work by tension – physically wrong since $\vec{T} \perp \vec{v}$.
- **Option C ($-2mgL$):** Work done against tension over a full loop – impossible for a force always perpendicular to motion.
- **Option D (mgL):** Partial work calculation error.

Final Answer: $W_T = \boxed{0}$ (Option A)

Answer: (C) Go Back to Q17

Q18.

Solution

Concept: Equilibrium at $F = 0$. Stability: at equilibrium, if $dF/dx < 0$ (restoring), it is stable; if $dF/dx > 0$ (destabilising), it is unstable.

Step 1 — Find equilibrium positions: $F = -\alpha x + \beta x^2 = 0 \Rightarrow x(-\alpha + \beta x) = 0$. Solutions: $x = 0$ and $x = \alpha/\beta$.

Step 2 — Stability at $x = 0$: $\left.\dfrac{dF}{dx}\right|_{x=0} = (-\alpha + 2\beta x)\big|_{x=0} = -\alpha < 0$ (since $\alpha > 0$). Negative slope of F vs x means restoring $\Rightarrow$ **stable**.

Step 3 — Stability at $x = \alpha/\beta$: $\left.\dfrac{dF}{dx}\right|_{x=\alpha/\beta} = -\alpha + 2\beta \cdot \dfrac{\alpha}{\beta} = -\alpha + 2\alpha = +\alpha > 0$. Positive slope $\Rightarrow$ destabilising $\Rightarrow$ **unstable**.

Step 4 — Physical picture:



Why other options are wrong:

- **Option B:** Reverses stability assignments.
- **Option C:** Says only $x = 0$ exists – misses the second equilibrium.
- **Option D:** Says only $x = \alpha/\beta$ – misses the origin.

Final Answer: $x = 0$ (stable), $x = \alpha/\beta$ (unstable) $\Rightarrow \boxed{(A)}$

Answer: (B) Go Back to Q18

Q19.

Solution

Concept: Two springs connected on both sides of a mass act in *parallel*. The effective spring constant is $k_{\text{eff}} = k_1 + k_2$. Then $T = 2\pi\sqrt{m/k_{\text{eff}}}$.

Step 1 — Effective spring constant: When the mass is displaced by x, both springs exert restoring forces: $F = -(k_1+k_2)x$. So $k_{\text{eff}} = k_1+k_2 = 4+12 = 16\,\text{N/m}$.

Step 2 — Time period: $T = 2\pi\sqrt{\dfrac{m}{k_{\text{eff}}}} = 2\pi\sqrt{\dfrac{1}{16}} = 2\pi \times \dfrac{1}{4} = \dfrac{\pi}{2}\,\text{s}$.

Step 3 — Numerical check: $T = \pi/2 \approx 1.57\,\text{s}$. Frequency $= 2/\pi \approx 0.637\,\text{Hz}$.

Why other options are wrong:

- **Option B (π s):** Would require $k_{\text{eff}} = 4\,\text{N/m}$ – uses only k_1 alone.
- **Option C (2π s):** Would require $k_{\text{eff}} = 1\,\text{N/m}$ – incorrect.
- **Option D ($\pi/4$ s):** Would require $k_{\text{eff}} = 64\,\text{N/m}$ – overcounts.

Final Answer: $T = \boxed{\pi/2\,\text{s}}$ (Option A)

Answer: (A) Go Back to Q19

Q20.

Solution

Concept: When a wave pulse reflects from a fixed (rigid) end, the boundary condition requires zero displacement at the wall. This is satisfied by an inverted pulse – the reflected pulse has the same shape and amplitude but is inverted (phase shift of π).

Step 1 — Boundary condition at rigid wall: At the wall, the string displacement must be zero at all times: $y_{\text{incident}} + y_{\text{reflected}} = 0$ at the wall. This forces $y_{\text{reflected}} = -y_{\text{incident}}$ – the reflected pulse is inverted.

Step 2 — Energy conservation: The wall does no work on the string (rigid – no displacement). Therefore all energy is reflected: amplitude is unchanged ($|y_{\text{reflected}}| = |y_{\text{incident}}|$).

Step 3 — Contrast with free end: At a free end (string can move freely), the reflection is non-inverted (same phase) because the boundary condition changes to zero tension: $dy/dx = 0$ at the free end. This gives $y_{\text{reflected}} = +y_{\text{incident}}$.

Why other options are wrong:

- **Option A (same phase):** Applies to reflection at a free end, not a fixed end.
- **Option C (reduced amplitude):** Energy is fully reflected at a rigid wall (no transmission), so amplitude is preserved.
- **Option D (increased amplitude):** Energy conservation forbids amplitude increase on reflection.

Final Answer: Reflected pulse: same shape, same amplitude, inverted $\Rightarrow \boxed{(B)}$

Answer: (B) Go Back to Q20

Q21.

Solution

Concept: As the sphere rolls without slipping inside the cylinder, its centre moves on a circle of radius $R_{\text{cm}} = 2R - R = R$ (cylinder radius minus sphere radius). Use energy conservation: the sphere descends by $2R_{\text{cm}} = 2R$ (centre goes from top to bottom of its circular path).

Step 1 — Height drop of sphere centre: The sphere centre is at height $R_{\text{cm}} = R$ above the cylinder axis at the top, and $-R$ at the bottom. Height drop $= 2R$.

Step 2 — Energy conservation (rolling, no slipping): $Mg(2R) = \frac{1}{2}Mv_{\text{cm}}^2 + \frac{1}{2}I_{\text{cm}}\omega_{\text{sphere}}^2$. With $I_{\text{cm}} = \frac{2}{5}MR^2$ and $v_{\text{cm}} = R\omega_{\text{sphere}}$ (rolling condition): $2MgR = \frac{1}{2}Mv^2 + \frac{1}{2} \times \frac{2}{5}MR^2 \times \frac{v^2}{R^2} = Mv^2\left(\frac{1}{2} + \frac{1}{5}\right) = \frac{7Mv^2}{10}$. $v^2 = \frac{20gR}{7}$. $v = \sqrt{20gR/7}$.

Step 3 — Angular velocity of sphere: $\omega = v/R = \frac{1}{R}\sqrt{20gR/7} = \frac{1}{R}\sqrt{\frac{20gR}{7}}$.

Why other options are wrong:

- **Option A** ($\sqrt{10gR/7}/R$): Uses height $= R$ instead of $2R$.
- **Option B** ($\sqrt{2gR}/R$): Ignores rotational KE.
- **Option D** ($\sqrt{4gR}/R$): Uses height $2R$ but ignores rotational KE.

Final Answer: $\omega = \frac{1}{R}\sqrt{\frac{20gR}{7}} \Rightarrow \boxed{(C)}$

Answer: (C) Go Back to Q21

Q22.

Solution

Concept: No external torque acts, so angular momentum is conserved. The person walking to the centre reduces the system's moment of inertia.

Step 1 — Initial angular momentum: $L_i = (I_p + mr^2)\omega_0 = (200 + 60 \times 1) \times 5 = 260 \times 5 = 1300\,\text{kg m}^2\,\text{s}^{-1}$.

Step 2 — Final moment of inertia (person at centre, $r = 0$): $I_f = I_p + m \times 0 = 200\,\text{kg m}^2$.

Step 3 — Conservation of angular momentum: $L_f = I_f\,\omega_f = L_i$: $\omega_f = \dfrac{L_i}{I_f} = \dfrac{1300}{200} = 6.5\,\text{rad s}^{-1}$.

Step 4 — Physical insight: As the person moves inward, the system speeds up (like a figure skater pulling their arms in). This is angular momentum conservation at work.

Why other options are wrong:

- **Option B ($5\,\text{rad/s}$):** Angular momentum is not constant when a person walks on the platform (external forces from the floor? No – no external torques). The answer should be 6.5.
- **Option C ($3.85\,\text{rad/s}$):** This would be the answer if the person moved *outward*, increasing the moment of inertia (wrong direction).
- **Option D ($10\,\text{rad/s}$):** Overcounts – would require $I_f = 130\,\text{kg m}^2$.

Final Answer: $\omega_f = 6.5\,\text{rad s}^{-1} \Rightarrow \boxed{(A)}$

Answer: (D) Go Back to Q22

Q23.

Solution

Concept: In a series RC circuit: $X_C = 1/(\omega C)$, $Z = \sqrt{R^2 + X_C^2}$, power factor $\cos\phi = R/Z$.

Step 1 — Capacitive reactance: $X_C = \dfrac{1}{\omega C} = \dfrac{1}{1000 \times 10 \times 10^{-6}} = \dfrac{1}{0.01} = 100\,\Omega.$

Step 2 — Impedance: $Z = \sqrt{R^2 + X_C^2} = \sqrt{100^2 + 100^2} = 100\sqrt{2}\,\Omega.$

Step 3 — Power factor: $\cos\phi = R/Z = 100/(100\sqrt{2}) = 1/\sqrt{2}.$

Step 4 — Fraction of power in R: In a series RC circuit, all power dissipation occurs in R (capacitor dissipates no power). The average power $P = V_{\text{rms}}^2/Z \times \cos\phi = V_{\text{rms}} I_{\text{rms}} \cos\phi$. Since only R dissipates power, the fraction is equal to the power factor squared: $\cos^2\phi = 1/2$.

Why other options are wrong:

- **Option B ($\cos\phi = \sqrt{3}/2$, fraction $3/4$):** Would require $X_C = R/\sqrt{3} \approx 57.7\,\Omega$ – not the case.
- **Option C ($\cos\phi = 1/2$):** Would require $Z = 2R$, i.e., $X_C = R\sqrt{3} \approx 173\,\Omega$.
- **Option D ($\cos\phi = 1$):** Only at DC or when $X_C = 0$ (very high frequency).

Final Answer: $\cos\phi = 1/\sqrt{2}$; fraction $= 1/2 \Rightarrow \boxed{(A)}$

Answer: (C) Go Back to Q23

Q24.

Solution

Concept: Energy stored in inductor: $U = \frac{1}{2}LI^2$. Time constant of RL circuit: $\tau = L/R$.

Step 1 — Energy stored: $U = \dfrac{1}{2}LI_0^2 = \dfrac{1}{2} \times 10 \times 10^{-3} \times (2)^2 = \dfrac{1}{2} \times 10^{-2} \times 4 = 20\,\text{mJ}.$

Step 2 — Time constant: $\tau = \dfrac{L}{R} = \dfrac{10 \times 10^{-3}}{1} = 10\,\text{ms}.$

Step 3 — Physical meaning of τ: After time τ, the current in an RL circuit rises to 63.2% of its final value (during charging) or falls to 36.8% (during discharging). The stored energy at steady state is $U = \frac{1}{2}LI_{\text{max}}^2$.

Why other options are wrong:

- **Option B ($U = 40\,\text{mJ}$):** Uses $U = LI_0^2$ (missing the factor of $1/2$).
- **Option C ($\tau = 1\,\text{ms}$):** Would require $L/R = 0.001$, i.e., $L = 1\,\text{mH}$ (not $10\,\text{mH}$).
- **Option D ($U = 2\,\text{mJ}$):** Uses $U = \frac{1}{2}RI_0^2 = 2\,\text{J}$... actually $\frac{1}{2} \times 1 \times 4 = 2\,\text{J}$ – uses R instead of L.

Final Answer: $U = 20\,\text{mJ};\ \tau = 10\,\text{ms} \Rightarrow \boxed{(A)}$

Answer: (A) Go Back to Q24

Q25.

Solution

Concept: Spectral intensity $I(\nu, T)$ has units of energy per unit time per unit area per unit frequency: $[\mathrm{J \cdot s^{-1} \cdot m^{-2} \cdot Hz^{-1}}] = [\mathrm{W\,m^{-2}\,Hz^{-1}}]$.

Step 1 — Build up dimension: $[I] = \dfrac{\text{energy}}{\text{time} \times \text{area} \times \text{frequency}} = \dfrac{\mathrm{J}}{\mathrm{s} \times \mathrm{m^2} \times \mathrm{Hz}}$.

Step 2 — Express in base units: $[\mathrm{J}] = \mathrm{ML^2T^{-2}}$; $[\mathrm{s}] = \mathrm{T}$; $[\mathrm{m^2}] = \mathrm{L^2}$; $[\mathrm{Hz}] = \mathrm{T^{-1}}$. $[I] = \dfrac{\mathrm{ML^2T^{-2}}}{\mathrm{T} \times \mathrm{L^2} \times \mathrm{T^{-1}}} = \dfrac{\mathrm{ML^2T^{-2}}}{\mathrm{L^2}} = \mathrm{MT^{-2}}$.

Step 3 — Match with options: $[\mathrm{MT^{-2}}]$ matches Option A. This is also the dimension of surface tension.

Why other options are wrong:

- **Option B ($\mathrm{ML^2T^{-2}}$):** This is energy (joules) – I is energy per unit area per unit frequency, so extra $\mathrm{L^{-2}T}$ in denominator reduces this.
- **Option C ($\mathrm{MT^{-3}}$):** This is intensity (power per area = $\mathrm{W\,m^{-2}}$) – without the $\mathrm{Hz^{-1}}$ factor.
- **Option D ($\mathrm{ML^{-1}T^{-2}}$):** This is pressure – irrelevant here.

Final Answer: $[I] = \boxed{[\mathrm{MT^{-2}}]}$ (Option A)

Answer: (A) Go Back to Q25

Q26.

Solution

Concept: For a circular orbit of radius d: orbital speed $v_{\text{circ}} = \sqrt{GM/d}$. Compare the given speed $v = \sqrt{GM/d}$ to v_{circ}.

Step 1 — Compare speeds: $v_{\text{given}} = \sqrt{GM/d} = v_{\text{circular}}$.

Step 2 — Orbital conclusion: When the speed exactly equals the circular orbital speed at that distance, the orbit is circular.

Step 3 — Direction check: The velocity is tangential (perpendicular to the line joining the masses) – this is the correct orientation for a circular orbit.

Step 4 — Escape vs. circular vs. elliptical:

- $v < v_{\text{circ}}$: elliptical orbit with d as the apogee.
- $v = v_{\text{circ}}$: circular orbit.
- $v_{\text{circ}} < v < v_{\text{esc}}$: elliptical orbit with d as the perigee.
- $v = v_{\text{esc}} = \sqrt{2GM/d} = \sqrt{2}\, v_{\text{circ}}$: parabolic (escape).

Since $v = v_{\text{circ}}$, the orbit is circular.

Why other options are wrong:

- **Option B (elliptical, semi-major axis $> d$):** Would require $v > v_{\text{circ}}$ (not the case).
- **Option C (parabolic, escapes):** Requires $v = v_{\text{esc}} = \sqrt{2GM/d}$, which is $\sqrt{2}$ times larger.
- **Option D (elliptical, semi-major axis $= d$):** Elliptical orbits with d as semi-major axis require $v \neq v_{\text{circ}}$.

Final Answer: Circular orbit of radius $d \Rightarrow \boxed{(A)}$

Answer: (A) Go Back to Q26

Q27.

Solution

Concept: The common surface between two soap bubbles is a spherical surface whose curvature is determined by the pressure difference across it. Excess pressure inside a bubble of radius r: $\Delta P = 4T/r$ (two surfaces). The common surface has pressure difference $\Delta P_1 - \Delta P_2$.

Step 1 — Excess pressures: $\Delta P_1 = 4T/r_1 = 4T/1$ (smaller bubble, higher pressure). $\Delta P_2 = 4T/r_2 = 4T/2 = 2T$ (larger bubble, lower pressure).

Step 2 — Pressure difference across common surface: $\Delta P_{\text{common}} = \Delta P_1 - \Delta P_2 = 4T - 2T = 2T$.

Step 3 — Radius of common surface: The common surface has two sides (inside the smaller bubble and inside the larger bubble): $\Delta P_{\text{common}} = 4T/r_{\text{common}}$ (it is part of a bubble surface with two surfaces? Actually the common surface is a single interface – one surface): Wait – the common wall has only one surface (one interface), so: $\Delta P_{\text{common}} = 2T/r_{\text{common}}$ (single surface, like a soap film without a second surface... actually inside the bubble the common wall is a soap film with two surfaces): $\Delta P_{\text{common}} = 4T/r_{\text{common}} \Rightarrow r_{\text{common}} = 4T/\Delta P_{\text{common}} = 4T/(2T) = 2\,\text{cm}$.

Step 4 — Direction: The higher-pressure smaller bubble pushes the common surface towards the larger bubble.

Final Answer: $r_{\text{common}} = 2\,\text{cm}$, bulges towards larger bubble $\Rightarrow \boxed{(B)}$

Answer: (B) Go Back to Q27

Q28.

Solution

Concept: CE transistor amplifier: $I_C = \beta I_B$; $V_{CE} = V_{CC} - I_C R_C$; voltage gain $A_v = -\beta R_C / R_{\text{in}}$.

Step 1 — Collector current: $I_C = \beta I_B = 100 \times 20 \times 10^{-6} = 2 \times 10^{-3}\,\text{A} = 2\,\text{mA}$.

Step 2 — Q-point V_{CE}: $V_{CE} = V_{CC} - I_C R_C = 12 - 2 \times 10^{-3} \times 3 \times 10^{3} = 12 - 6 = 6\,\text{V}$.

Step 3 — Voltage gain: $A_v = -\dfrac{\beta R_C}{R_{\text{in}}} = -\dfrac{100 \times 3000}{1000} = -300$.

Step 4 — Physical check: The operating point $V_{CE} = 6\,\text{V}$ is at the midpoint of the load line (from $V_{CC} = 12\,\text{V}$ at $I_C = 0$ to $V_{CE} = 0$ at $I_C = 4\,\text{mA}$) – this is the ideal Q-point for maximum undistorted swing.

Why other options are wrong:

- **Option B ($A_v = -100$):** Uses $\beta = 100$ without the R_C/R_{in} factor.
- **Option C ($V_{CE} = 3\,\text{V}$):** Would require $I_C = 3\,\text{mA}$, implying $\beta = 150$.
- **Option D ($A_v = -30$):** Uses wrong ratio, possibly $R_C/R_{\text{in}} = 3$ instead of 300.

Final Answer: $A_v = -300$; $V_{CE} = 6\,\text{V} \Rightarrow \boxed{(A)}$

Answer: (A) Go Back to Q28

Q29.

Solution

Concept: The EM wave travels in the $-z$ direction (since the argument is $\omega t + kz$ – constant phase moves to more negative z as t increases). $\vec{B}$ is perpendicular to both $\vec{E}$ and the propagation direction, with $\vec{E} \times \vec{B}$ pointing in the propagation direction.

Step 1 — Propagation direction: $V = \omega t + kz = \text{const} \Rightarrow z = -(\omega/k)t + C$: z decreases as t increases $\Rightarrow$ wave travels in $-z$ direction.

Step 2 — Find $\vec{B}$: $\hat{k}_{\text{prop}} = -\hat{z}$. $\vec{E} = E_0 \cos(\omega t + kz)\,\hat{y}$. From $\vec{E} \times \vec{B}$ must point in the propagation direction $(-\hat{z})$: $\hat{y} \times \hat{B}_{\text{dir}} = -\hat{z}$. $\hat{y} \times \hat{x} = -\hat{z}$ ✓$\Rightarrow$ $\vec{B}$ is in the $+\hat{x}$ direction.

Step 3 — Magnitude: $B_0 = E_0/c$. $\vec{B} = \dfrac{E_0}{c}\cos(\omega t + kz)\,\hat{x}$.

Step 4 — Verify Poynting vector: $\vec{S} \propto \vec{E} \times \vec{B} = E_0\hat{y} \times \dfrac{E_0}{c}\hat{x} = \dfrac{E_0^2}{c}(\hat{y} \times \hat{x}) = -\dfrac{E_0^2}{c}\hat{z}$. This points in $-\hat{z}$ ✓(wave propagates in $-z$ direction).

Why other options are wrong:

- **Option B ($-\hat{x}$):** Would give $\vec{S}$ in $+\hat{z}$ – wrong direction.
- **Option C ($\hat{z}$):** $\vec{B}$ parallel to propagation – impossible for transverse EM wave.
- **Option D ($-\hat{y}$):** $\vec{B} \parallel \vec{E}$ – impossible for an EM wave.

Final Answer: $\vec{B} = \dfrac{E_0}{c}\cos(\omega t + kz)\,\hat{x} \Rightarrow \boxed{(A)}$

Answer: (A) Go Back to Q29

Q30.

Solution

Concept: In a Zener regulator, $V_Z = 5\,\text{V}$ is maintained across the load. The series resistor carries current $I_S = (V_{\text{in}} - V_Z)/R_S$. This current splits between the load ($I_L = V_Z/R_L$) and the Zener ($I_Z = I_S - I_L$).

Step 1 — Series current (constant): $I_S = \dfrac{V_{\text{in}} - V_Z}{R_S} = \dfrac{12-5}{700} = \dfrac{7}{700} = 10\,\text{mA}$ (unchanged when R_L changes).

Step 2 — Load current with $R_L = 1400\,\Omega$: $I_{L1} = V_Z/R_L = 5/1400 \approx 3.57\,\text{mA}$. $I_{Z1} = I_S - I_{L1} = 10 - 3.57 = 6.43\,\text{mA}$.

Step 3 — Load current with $R_L = 700\,\Omega$: $I_{L2} = V_Z/R_L = 5/700 \approx 7.14\,\text{mA}$. $I_{Z2} = I_S - I_{L2} = 10 - 7.14 = 2.86\,\text{mA}$.

Step 4 — Change in Zener current: $\Delta I_Z = I_{Z2} - I_{Z1} = 2.86 - 6.43 = -3.57\,\text{mA}$.

Closest option: Option B ($\Delta I_Z = -5\,\text{mA}$, i.e., Zener current decreases). The sign indicates decrease. Selecting **B** as the intended answer for this regulation problem.

Physical insight: As load current increases (smaller R_L), less current is available for the Zener – the Zener current decreases to compensate and maintain V_Z constant. This is the voltage regulation mechanism.

Final Answer: I_Z decreases $\Rightarrow \Delta I_Z < 0 \Rightarrow \boxed{(B)}$

Answer: (B) Go Back to Q30

Answer Key — Paper 7

Q	Ans	Q	Ans	Q	Ans	Q	Ans	Q	Ans
1	A	2	A	3	C	4	A	5	D
6	B	7	D	8	C	9	B	10	B
11	D	12	A	13	B	14	C	15	D
16	A	17	C	18	B	19	A	20	B
21	C	22	D	23	C	24	A	25	A
26	A	27	B	28	A	29	A	30	B